

**PAT-NO:** JP361288004A  
**DOCUMENT-IDENTIFIER:** JP 61288004 A  
**TITLE:** UTILIZING METHOD FOR  
CONVERTER WASTE GAS  
**PUBN-DATE:** December 18, 1986

**INVENTOR-INFORMATION:**

NAME	COUNTRY
KATAYAMA, EIJI	
HAMADA, HISAO	
TAKADA, SHIKO	
TAKEUCHI, SHINOBU	
USHIJIMA, TAKASHI	
IGAWA, KATSUTOSHI	

**ASSIGNEE-INFORMATION:**

NAME	COUNTRY
KAWASAKI STEEL CORP	N/A

**APPL-NO:** JP60128805  
**APPL-DATE:** June 13, 1985

**INT-CL (IPC):** C21B013/00 , C22B005/12 ,  
C21C005/38

**US-CL-CURRENT:** 75/444

**ABSTRACT:**

PURPOSE: To effectively utilize converter waste

gas by introducing the converter waste gas into a carbonaceous material fluidized bed and converting the gas then storing such gas, further increasing the temp. of the stored gas and introducing the gas into a powdery iron ore fluidized bed thereby reducing the iron ore.

CONSTITUTION: The carbonaceous material is charged through a charging port 6 into the fluidized bed 5 and the converter waste gas under blowing is introduced into the fluidized bed 5 as the 1st stage. The CO<sub>2</sub> and H<sub>2</sub> in the gas are converted to CO, H<sub>2</sub> by the above-mentioned carbonaceous material and the gas is once stored in a gas holder 19. The above-mentioned carbonaceous material is discharged from a discharge port 8 of the fluidized bed 5 and thereafter the preheated iron ore is charged through the port 6 into the fluidized bed as the 2nd stage. The stored gas is then introduced by an intensifying blower 10 into the fluidized bed 5 and part of the gas is partially burned to increase the temp. of the gas to a prescribed temp. The iron ore is thereby reduced. The iron ore after the reduction is discharged from a discharge port 7. The converter gas is thus effectively utilized for the gas conversion and the ore reduction without receiving the restriction for the blowing time of the converter 1.

COPYRIGHT: (C)1986,JPO&Japio